

PRODUCT DESCRIPTION

APP 111 acrylic ester building sealant is a one-component, neutral curing acrylic sealant adhesive, specially used for sealing the gaps between window & door and walls.

PRODUCT PROPERTY

One component, fast deep curing, suitable for factory working, high strength and modulus, neutral curing.

TYPICAL APPLICATIONS

Sealing of joints around doors, windows and balconies. Sealing of indoor decoration with leak proof, dust-proof and thermal insulation functions. Joint sealing of gypsum board, straw board and other boards.

TECHNICAL DATA

Item	Typical value	
Appearance	White paste	
Density(g/cm3)	1.56~1.62	
PH	7.0~9.0	
Constant elongation adhesion	No damage	
Tack free time	25~45min	
Hardness (Shore A)	20~40	
Heating aging	Thermal weightlessness, %	≤8.0
	Crack	Non
	Pulverization	Non

DIRECTIONS FOR USE

Clean & dry contact surface, get rid of rust, dust and oil, use solvent if necessary.
Use glue gun to dispense the adhesives to the contact surface.
Any modifications should be cared out before curing to insure a prestine finish.

CAUTIONS

Do not use for structure sealing. Do not use for all materials that exudes oil, plasticizer & solvent, such as oiled woods. Do not use in a inclosed environment without moisture as the curing needs moisture. Do not use on frosty or humid surfaces.

PACKAGE

280ml/ cartridge, 24 cartridges/ carton.

STORAGE

Store at 8-28 °C in a cool and dry place 18 months.

NOTE

The information contained herein is believed to be reliable. Due to the wide range of actual conditions, it is impossible for us to have a comprehensive understanding of everything, so we cannot guarantee the correctness and suitability of our product for certain usage and purposes. Users should have a detailed understanding of the product before using it, and then decide for themselves the best way to use it.