

PRODUCT DESCRIPTION

APP 335 is a general-purpose silicone construction sealant specially designed for sealing doors, windows, internal and external wall joints. It has good adhesion to a wide range of doors, windows and construction substrates, and is also suitable for general sealing, including glass, ceramic tiles, concrete, masonry and aluminium, etc. It is a single-component, neutral curing, and does not corrode the substrate.

PRODUCT FEATURES

- One-part, neutral curing
- Good extrudability and thixotropy
- Excellent adhesion to a wide range of substrates
- Outstanding weathering resistance, reliable long life
- Eco-friendly, non-corrosive, non-irritating gas

TYPICAL APPLICATIONS

- Suitable for all kinds of doors and window installation, glass assembly
- Suitable for waterproof sealing of window sash
- Seam sealing for various other applications

TYPICAL TECHNICAL DATA (real values may have deviations)

Sagging, mm		≤2
Extrusion , ml/min		≥50
Tack-free time, h		≤48
Density, g/cm ³		1.23
Tensile strength, ISO 527, MPa		0.42
Elongation performance after Hot Air-Water Cycle		No damage
Elongation performance after Water-UV Irradiation		No damage
Flexibility at low temperature, -10°C		Qualified
Recovery ratio after Hot Air-Water cycle		≥80
Tension - Compression	Durability grade	8020
Cycle performance	Bonding failure area, %	0

*This product meets the standard:GB/14683 JC/T 485



DIRECTIONS FOR USE

Firstly ensure that the contact surfaces are clean and dry. Remove rust, dust, oil, etc. If necessary, use solvents for cleaning and drying. Apply protective material to the area to be protected but do not touch the surface to be glued. Use a glue gun to squeeze the glue from the cartridge into the interface area. When corrections are required, it is important to do so before the glue has cured to ensure a flat and aesthetic appearance.

STORAGE & TRANSPORTATION

Recommended transportation environment	Optimal environment: 5~27°C, <70%RH; avoid sunshine, rain, humidity, impact, and extrusion of packing.
Recommended storage temperature	5~27°C
Storage environment	Cool, dry
Shelf life	12 months

PACKING SPECIFICATION

APP 335, 300ml/cartridge; 500ml/sausage; 590ml/sausage

COLOUR

Available in different colors such as black, white, grey and translucent

CAUTIONS

Keep away from children for storage.
If the eyes are accidentally exposed to the product, rinse immediately with water, and seek medical attention.
It is recommended to use the product in a well-ventilated place.
Please consult the MSDS of the product for safety information.

APPLICATION LIMITS

Cannot be used as a structural sealant.
Not suitable for use on all materials that leach grease, plasticisers or solvents.
e.g. surfaces of oil-impregnated wood
Not suitable for use in closed, moisture-free environments, as the sealant needs to absorb moisture from the air to cure.
Not suitable for use on frosted or wet surfaces.
Not suitable for use in areas that are continuously flooded or wet all year round.

NOTE

The information contained herein is believed to be reliable. Due to the wide range of actual conditions, it is impossible for us to have a comprehensive understanding of everything, so we cannot guarantee the correctness and suitability of our product for certain usage and purposes. Users should have a detailed understanding of the product before using it, and then decide for themselves the best way to use it.